

Zestawienie robót w zakresie wykonania odwodnienia i rowów

		pobocze umocnione mat.kamiennym			renowacja- odmulenie rowów	umocnienie ie dna rowu	umocnienie skarp płyty ECO 40x60	umocnienie skarp płyty 50x50x7
	strona prawa	dł.	szer	pow.				
		m	m	m2	mb	mb	m2	
od km	do km							
0+450	0+500	45,0	0,75	33,8	45,0			
0+500	0+600	90,0	0,75	67,5	90,0			
0+600	0+700	90,0	0,75	67,5	90,0			
0+700	0+800	100,0	0,75	75,0	100,0			
0+800	0+900	100,0	0,75	75,0	100,0			
0+900	1+000	70,0	0,75	52,5	70,0			
1+000	1+100	100,0	0,75	75,0	100,0			
1+100	1+200	95,0	0,75	71,3	95,0			
1+200	1+281,16	80,0	0,75	60,0	80,0			
1+281,16	1+300	20,0	0,75	15,0	20,0			
1+300	1+400	100,0	0,75	75,0	100,0			
1+400	1+500	95,0	0,75	71,3	95,0			
1+500	1+600	95,0	0,75	71,3	95,0			
1+600	1+700	100,0	0,75	75,0	80,0			
1+700	1+800	100,0	0,75	75,0				
1+800	1+900	90,0	0,75	67,5				
1+900	2+000	100,0	0,75	75,0				
2+100	2+200	65,0	0,75	48,8				
2+200	2+214,4		0,75	0,0				
		1535,0		1151,5	1 160,0	0,00	0,00	0,00

Renowacja rowów ujęta w pozycji robory ziemne